
DF 91009859



SBI Allocation Between Heavy and Singlet Missiles

19980513 12

DISTRIBUTION STATEMENT A

Approved for relative release;
Distribution Schinited

DITC COARSON BUILDINGS .

PLEASE RETURN TO:

BMD TECHNICAL INFORMATION CENTER BALLISTIC MISSILE DEFENSE ORGANIZATION 7100 DEFENSE PENTAGON WASHINGTON D.C. 20301-7100

Los Alamos

Los Alamos National Laboratory is operated by the University of California for the United States Department of Energy under contract W-7405-ENG-36.

Prepared by Bo West, P Division An Affirmative Action/Equal Opportunity Employer This report was prepared as an account of work sponsored by an agency of the This report was prepared as an account of work sponsored by an agency of the United States Government. Neither The Regents of the University of California, the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by The Regents of the University of California, the United States Construment or any agency thereof. The views

of the University of California, the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of The Regents of

the University of California, the United States Government or any agency thereof.

Accession Number: 3154

Publication Date: Apr 01, 1991

Title: SBI Allocation Between Heavy and Singlet Missiles

Personal Author: Canavan, G. H.

Corporate Author Or Publisher: Los Alamos National Laboratory, Los Alamos, New Mexico 87545 Report Number: LA-11888-MS

Report Prepared for: U.S. Department of Energy, Washington, DC

Descriptors, Keywords: SBI Missile Singlet RV Penetration SDI

Pages: 00007

Cataloged Date: Sep 25, 1991

Contract Number: W-7405-ENG-36

Document Type: HC

Number of Copies In Library: 000001

Original Source Number: DE91-009859

Record ID: 22614

Source of Document: DOE

UC-900 and UC-700 Issued: April 1991

SBI Allocation Between Heavy and Singlet Missiles

Gregory H. Canavan

CONTENTS

ABSTRACT	1
I. INTRODUCTION	1
II. HEAVY MISSILE ANALYSIS	2
III. SINGLET MISSILES	3
IV. TOTAL PENETRATION	_. 3
V. OBSERVATIONS	4
REFERENCES	6

SBI ALLOCATION BETWEEN HEAVY AND SINGLET MISSILES

by

Gregory H. Canavan

ABSTRACT

The optimal allocation of space-based interceptors (SBIs) between fixed, heavy missiles and mobile singlets can be derived from approximate expressions for the boost-phase penetration of each. Singlets can cluster before launch and have shorter burn times, which reduce their availability to SBIs by an order of magnitude. Singlet penetration decreases slowly with the number of SBIs allocated to them; heavy missile penetration falls rapidly. The allocation to the heavy missiles falls linearly with their number. The penetration of heavy and singlet missiles is proportional to their numbers and inversely proportional to their availability.

I. INTRODUCTION

This paper derives and discusses the optimal allocation of SBIs between fixed heavy missiles and mobile single reentry vehicle (RV) missiles. As the fraction of the SBIs allocated to singlets increases, the number of penetrating singlets increases slowly but the numbers of heavy missile RVs falls rapidly. Thus, for large numbers of heavy missiles, all of the SBIs are allocated to them. For small numbers their allocation falls and

the penetrating heavy and singlet RVs is proportional to their numbers and inversely proportional to their availabilities.

II. HEAVY MISSILE ANALYSIS

The geometric fraction of a K SBI constellation within range of the land missile launch area is

$$f = z\pi (W+VT)^2/4\pi R_0^2, \qquad (1)$$

where $R_e \approx 6,400$ km is the Earth's radius, W is the effective radius of the launch area, V is the SBI divert velocity, T is the missile burn time, and $z \approx 2.5/\sqrt{(W+VT)}$ is a numerical factor representing the constellation concentration possible over launch areas of modest latitudinal extent. For the current T = 600 s for heavy missiles, the current T = 600 s representing the missiles in the current T = 600 s Relocating the missiles in the current T = 600 s launch area, which has a radius of $T \approx 600$ km, would give $T \approx 600$ s. Thus, the number of SBIs required for one intercept per missile is

 $K = zK[(W+VT)/2R_e]^2$. (2) The constellations must be oversized by 30-50% to destroy most of the RVs before they are released. The sizes can be calculated exactly for single engagements³ and approximately for two,⁴ but the results are awkward for survey calculations. However, a simple approximation of acceptable accuracy is available.⁵

The approximation is based on the observation that the exact number of RVs killed, R, is linear in m_OpK for small K and rolls over at K \approx M/f, where the number of SBIs in range approaches the number of missiles launched, M; m_O is the initial number of RVs per missile, and p \approx 1 is the SBIs' probability of kill. The simplest analytic function with these properties is

 $R \approx m_O p M[1 - exp(-fK/M)],$ (3) which for K small is $\approx m_O p M(fK/M) \approx m_O p f K$, i.e., the product of the SBIs available, fK, and the average RVs killed by each in a target-rich environment, $m_O p$. For large K, $R \approx m_O p M$, i.e. all of the RVs are killed. The fraction penetrating is in general

$$P = 1 - R/m_0 pM \approx e^{-fK/M}$$
, (4)
which is exact for both small and large K. The intermediate
behavior is only approximately correct.⁶ The main discrepancy is

near K \approx M/f, where the exact result gives 10-20% more kills than the approximation. The differences are similar in current, START, and midterm force levels.

The approximation falls off too gently compared to the exact result; it thus consistently underestimates the number of RV kills and overestimates the number of RVs penetrating. The exact formulae could be used, but if the calculations are used to size boost phases with midcourse underlays, the uncertainties in the boost phase could at worst double the demands on the midcourse layer, which is generally a minor part of the total.

III. SINGLET MISSILES

The analysis for mobile singlets largely follows from that for heavy missiles. For the S singlets m = 1. Because they can cluster at a point before launch, their geometric availability is that of Eq. (1) for W = 0, which is

$$j = z\pi (VT)^2/4\pi R_e^2$$
, (5) where z is still 2.5//(W+VT) \approx 1.24, because SBI constellations must be optimized for the heavy missiles, so long as they are dominant. Thus, the number of singlets that would penetrate K SBIs is roughly Se^{-jK/S}. For singlets with T \approx 300 s, $j \approx$ 0.03.

IV. TOTAL PENETRATION

If a fraction ϕ of the SBIs were allocated to the heavy missiles and the rest to the singlets, the total number of penetrating RVs would be

$$V = Se^{-j(1-\phi)K/S} + m_0Me^{-f\phi K/M}, \qquad (6)$$
 which is shown as a function of ϕ in Fig. 1 for $m = 10$, $M = 100$, $K = 4,000$ SBIs, and $S = 344$ singlets. The curves are for $f = 0.13$ and $j = 0.03$, which correspond to concentration of both the heavy and singlet missiles in the current Soviet heavy missile launch area in the near-term.

For ϕ small the bottom curve is the number of penetrating singlets, which increases slowly with ϕ ; the middle curve is the number of penetrating heavy RVs, which falls rapidly. The top

curve is their total, V, which has a weak minimum at about $\phi \approx 70\%$ of the SBIs allocated to the heavy missiles.

The defender wishes to minimize V, which he does by differentiating V with respect to ϕ , setting the result to zero, and solving for

 $\phi_{\rm O}=[\ln({\rm mf/j})+{\rm jK/S}]/({\rm j/S}+{\rm f/M}){\rm K}$ (7) as the allocation that minimizes overall penetration. The optimal $\phi_{\rm O}$ is shown as a function of M by the top curve in the middle in Fig. 2. The lower curves are the total, heavy, and single RV contributions for those M and $\phi_{\rm O}$. The optimal $\phi_{\rm O}$ is unity for M > 150; below that it falls linearly with M. The singlet missiles are not attacked for larger M; below M = 150 they fall slowly. The heavy missiles fall strongly for M > 150; after that they also fall slowly. For nominal conditions, $\phi_{\rm O}\approx [\ln({\rm mf/j})]{\rm M/fK}$, so the number of penetrating heavy RVs is about jM/f, and the number of penetrating heavy and singlet RVs is in the ratio M/f:S/j.

For the current START M \approx 270 heavy and S \approx 344 singlet Soviet missiles ϕ_0 = 1; i.e., all SBIs are allocated to heavy missiles and the singlets get a free ride. Heavy and singlet contributions are about equal at M = 250. Below M = 150 they are attrited proportionally, although there is little contribution left from heavy missiles at that point.

V. OBSERVATIONS

It is possible to derive the optimal allocation of SBIs between fixed heavy missiles and mobile single RV missiles if approximate expressions are used for the penetration of each. Singlet missiles are distinguished by their ability to cluster before launch and shorter booster burn times, which gives the SBIs an order of magnitude less availability for them.

The number of penetrating singlets decreases slowly with the allocation of SBIs to them; the number of penetrating heavy RVs falls rapidly. Their sum has a weak minimum at intermediate allocations to heavy missiles. The defender can minimize the total number of penetrating RVs by allocating the SBIs according

to analytic criteria. For large numbers of heavy missiles, all SBIs are allocated to them. For small numbers their allocation falls linearly with their numbers, and the penetration of heavy and singlet RVs is proportional to their numbers and inversely proportional to their availability.

The proportional allocation applies to two distinct, relevant cases. The first is restrike. If one side rides out the other's first strike before launching, given current accuracies it is likely that the number of missiles in the restrike will fall below the transition. That appears to be of academic interest only to the U.S., whose mobile options are waning. It would, however, be relevant to U.S. allocation of its SBIs between Soviet singlets and residual heavy missiles, if the U.S. struck first, which is now, however, thought to be an unlikely eventuality.

The other case is the postulated build down from heavy missiles to mobile singlets. At about half the current level of Soviet heavy missiles, SBI allocation would begin to shift to singlets. The shift would, however, be too gradual to impact earlier studies of the stability of the transition.⁸

REFERENCES

- 1. G. Canavan, "Geometric Defensive Satellite Constellation Concentration," Los Alamos National Laboratory document LA-UR-89-3887, November 1989.
- 2. R. Garwin, "How Many Orbiting Lasers for Boost-Phase Intercept?," Nature, 315, 23 May 1985, pp. 286-90.
- 3. G. Canavan, "Average Deployments vs Missile and Defender Parameters," Los Alamos National Laboratory report LA-11856-MS, April 1990.
- 4. G. Canavan, "Scaling of SBI Second Shots," Los Alamos National Laboratory document LA-UR-90-draft, May 1990.
- 5. G. Canavan, "Approximate Average Deployments Versus Defensive Parameters," Los Alamos National Laboratory document LA-11880-MS, April 1990.
- 6. G. Canavan, "Approximate Average Deployments versus Defensive Parameters," op. cit.
- 7. G. Canavan, "Interaction of Strategic Defenses with Crisis Stability," Los Alamos National Laboratory report LA-11870-MS, April 1990, Appendix C.
- 8. G. Canavan, "Interaction of Strategic Defenses with Crisis Stability," Los Alamos National Laboratory report LA-11870-MS, April 1990.

Fig. 1 Penetrating RVs vs allocation





Fig.2 Optimal allocations & pen. RVs



This report has been reproduced directly from the best available copy.

It is available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62,
Oak Ridge, TN 37831.
Prices are available from (615) 576-8401, FTS 626-8401.

It is available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.