
Advantage of Base-Line Redundancy in Sparse Apertures

Study Leader:
F. Dyson

September 2000

JSR-2000-551

Approved for public release; distribution unlimited.

JASON
The MITRE Corporation
1820 Dolley Madison Boulevard
McLean, Virginia 22102-3481
(703) 883-6997

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information estimated to average 1 hour per response, including the time for review instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE September 27, 2000	3. REPORT TYPE AND DATES COVERED	
4. TITLE AND SUBTITLE Advantage of Base-line Redundancy in Sparse Apertures			5. FUNDING NUMBERS 13-988534-A4	
6. AUTHOR(S) F. Dyson				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) The MITRE Corporation JASON Program Office 1820 Dolley Madison Blvd McLean, Virginia 22102			8. PERFORMING ORGANIZATION REPORT NUMBER JSR-2000-551	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) National Reconnaissance Office 14675 Lee Road Chantilly, Virginia 20151			10. SPONSORING/MONITORING AGENCY REPORT NUMBER JSR-2000-551	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE Distribution Statement A	
13. ABSTRACT <i>(Maximum 200 words)</i> A general argument is presented to explain the dependence of observation-time T on sparseness f in observations with sparse apertures. For a system using a single observation, $T \sim f^{-3}$, while for a system using multiple observations, $T \sim f^{-2}$. When multiple observations are used, the optimum strategy is to maximize the redundancy of base-lines within each observation but to minimize the redundancy of base-lines between observations.				
14. SUBJECT TERMS			15. NUMBER OF PAGES	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT SAR	

Abstract

A general argument is presented to explain the dependence of observation-time T on sparseness f in observations with sparse apertures. For a system using a single observation, $T \sim f^{-3}$, while for a system using multiple observations, $T \sim f^{-2}$. When multiple observations are used, the optimum strategy is to maximize the redundancy of base-lines within each observation but to minimize the redundancy of base-lines between observations.

We consider an imaging system designed to achieve optimum signal-to-noise ratio when observing a scene with uniform bright-field background. The resolution and field-of-view are chosen to be equivalent to the diffraction-limited resolution and field-of-view of a filled aperture telescope of given size, but the actual system uses a sparse-aperture telescope covering a fraction f of the filled aperture. We suppose that the number of pixels in the diffraction-limited image is N . The filled aperture can usefully be considered as consisting of N patches and the sparse aperture as consisting of fN patches. Each Fourier component of the image brightness is the result of interference of light reflected from two patches of the aperture, with a base-line equal to the vector separation of the two patches. There is a one-to-one correspondence between Fourier components of the image and base-lines of the aperture. We use the index $k = 1, 2, \dots, N$ to refer to both Fourier components and base-lines. The same label k refers also to the Fourier components of the brightness of the scene.

In order to obtain full resolution of the scene, it is essential to use apertures including all base-lines. To obtain uniform resolution of details, it is desirable to cover all base-lines as uniformly as possible. But there are two ways to achieve uniform coverage of base-lines. Method 1 uses a single sparse aperture covering all base-lines. Method 2 divides the observation of a single scene into n intervals of time, using n different sparse apertures for the observations. Using Method 2, each individual aperture does not need to cover all base-lines. It is sufficient if the apertures collectively cover all base-lines. In Method 2, the number n of observations is to be chosen to optimize the signal-to-noise ratio of the image obtained by combining n observations

within a total duration T . Method 1 is the special case of Method 2 when $n = 1$, so there is only a single observation of duration T . The n observations are labeled by the index $m = 1, 2, \dots, n$.

Let R_{km} be the redundancy of base-line k in the aperture used for observation m , i.e., the number of pairs of patches in that antenna separated by the vector k . For each observation, the sum of the redundancies is equal to the number of pairs of patches,

$$\sum_k R_{km} = \frac{1}{2} f^2 N^2, \quad m = 1, \dots, n. \quad (1)$$

Now consider the signal S_{km} and noise N_{km} in the observation m of Fourier component k of the scene

$$S_{km} = (T/n) R_{km} B_k, \quad (2)$$

$$N_{km} = [(T/n) R_{0m} U]^{1/2} = [(T/n) f N U]^{1/2}, \quad (3)$$

where B_k is the brightness of Fourier component k of the scene, U is the uniform background brightness, and $R_{0m} = fN$ is the number of patches in the antenna for each observation.

The best estimate of the scene brightness B_k is a linear combination of the signals S_{km} ,

$$E_k = (n/T) \sum_m (R_{km}/V_k) S_{km}, \quad (4)$$

$$V_k = \sum_m R_{km}^2, \quad (5)$$

each weighted in proportion to its signal-to-noise ratio. E_k is Fourier component k of the best image that can be reconstructed from the n observations. The estimate E_k measures B_k with noise

$$W_k = [n f N U / T V_k]^{1/2}, \quad (6)$$

according to (3) and (4). To obtain an image with uniformly low noise, all the W_k should be small.

We take as figure-of-merit for the system as a whole the root-mean-square signal-to-noise ratio of all the Fourier components of the image,

$$\begin{aligned} F &= [\sum_k E_k^2 / \sum_k W_k^2]^{1/2} \\ &= \left[\frac{TB^2}{nfU} \right]^{1/2} \left[\sum_k \frac{1}{V_k} \right]^{-1/2}, \end{aligned} \quad (7)$$

where

$$B = \left[\frac{1}{N} \sum_k B_k^2 \right]^{1/2} \quad (8)$$

is the root-mean-square signal. To make (7) large, all the sums (5) should be uniformly as large as possible. Let

$$Y_k = \sum_m R_{km} \quad (9)$$

be the total redundancy of base-line k in all the n observations. The sum of the Y_k is fixed by (1),

$$\sum_k Y_k = \frac{1}{2} n f^2 N^2. \quad (10)$$

To make (7) large, we should first distribute the total redundancy as equally as possible over the base-lines, so that all the Y_k are roughly equal to the average

$$Y_k \sim Y = \frac{1}{2} n f^2 N, \quad (11)$$

and then distribute the redundancy of each base-line as unequally as possible over the observations, so that one or two terms R_{km}^2 dominate in each sum (5). So far as possible, each base-line should be used in only one of the n observations. The system is optimized when the redundancies are minimized

between observations and maximized within observations. If this is done, each V_k is approximately equal to the square of the corresponding Y_k ,

$$V_k \sim Y_k^2 \sim \frac{1}{4}n^2 f^4 N^2 \quad (12)$$

according to (11). But the maximum redundancy of any base-line in any observation is fN , so that

$$V_k \leq fNY_k \sim \frac{1}{2}nf^3 N^2, \quad (13)$$

by (11). Comparing (12) with (13),

$$fn \leq 2. \quad (14)$$

The maximum number of observations that can be combined efficiently is

$$n_{\max} = 2f^{-1}. \quad (15)$$

For geometrical reasons, it is not possible to use all base-lines in exactly one observation each. The shortest base-lines will necessarily appear in all the observations. But the majority of base-lines are not short, and it should be possible to arrange for the long ones to appear in only one or two observations. The approximate equality (12) will then hold for the majority of base-lines.

When (12) holds, the figure-of-merit of the system according to (7) is

$$F = [(B^2 N/4U)nf^3 T]^{1/2}. \quad (16)$$

For a given scene brightness B , background brightness U , and signal-to-noise ratio F , the total observation-time T varies with n and f according to

$$T \sim (nf^3)^{-1}. \quad (17)$$

This means that for a system using only one observation (Method 1),

$$T \sim f^{-3}, \quad (18)$$

while for a system using the optimum number (15) of observations (Method 2),

$$T \sim f^{-2}. \quad (19)$$

In particular, a system using a single observation with a ring-shaped or Y-shaped antenna will have $T \sim f^{-3}$, while a system with a rotating rectangular antenna observing in $(2f^{-1})$ different orientations will have $T \sim f^{-2}$. The rectangular antenna is in principle more efficient when f is very small. For practical values of f , the theoretical advantage of multiple observations may be insignificant, and a system using a single observation may be preferred for other reasons.

DISTRIBUTION LIST

Director of Space and SDI Programs
SAF/AQSC
1060 Air Force Pentagon
Washington, DC 20330-1060

CMDR & Program Executive Officer
U S Army/CSSD-ZA
Strategic Defense Command
PO Box 15280
Arlington, VA 22215-0150

Superintendent
Code 1424
Attn Documents Librarian
Naval Postgraduate School
Monterey, CA 93943

DTIC [2]
8725 John Jay Kingman Road
Suite 0944
Fort Belvoir, VA 22060-6218

Dr. A. Michael Andrews
Director of Technology
SARD-TT
Room 3E480
Research Development Acquisition
103 Army Pentagon
Washington, DC 20301-0103

Dr. Albert Brandenstein
Chief Scientist
Office of Nat'l Drug Control Policy
Executive Office of the President
Washington, DC 20500

Dr. H. Lee Buchanan, III
Assistant Secretary of the Navy
(Research, Development & Acquisition)
3701 North Fairfax Drive
1000 Navy Pentagon
Washington, DC 20350-1000

Dr. Collier
Chief Scientist
U S Army Strategic Defense Command
PO Box 15280
Arlington, VA 22215-0280

DARPA Library
3701 North Fairfax Drive
Arlington, VA 22209-2308

Dr. Martin C. Faga
President and Chief Exec Officer
The MITRE Corporation
A210
202 Burlington Road
Bedford, MA 01730-1420

Mr. Frank Fernandez
Director
DARPA/DIRO
3701 North Fairfax Drive
Arlington, VA 22203-1714

Mr. Dan Flynn [5]
Program Manager
DI/OT/SAB
DI/OTI/SAG
5 S 49 NHB
Washington, DC 20505

Dr. Paris Genalis
Deputy Director
OUSD(A&T)/S&TS/NW
The Pentagon, Room 3D1048
Washington, DC 20301

Dr. Lawrence K. Gershwin
NIO/S&T
2E42, OHB
Washington, DC 20505

General Thomas F. Gioconda [5]
Assistant Secretary for Defense
US Department of Energy
DP-1, Room 4A019
Mailstop 4A-028
1000 Independence Ave, SW
Washington, DC 20585

Lee Hammarstrom
National Reconnaissance Office
14675 Lee Road
Chantilly, VA 20151

Dr. Theodore Hardebeck
STRATCOM/J5B
Offutt AFBNE68113

DISTRIBUTION LIST

Mr. David Havlik
Manager
Weapons Program Coordination Office
MS 9006
Sandia National Laboratories
PO Box 969
Livermore, CA94551-0969

Dr. Helmut Hellwig
Deputy Asst Secretary
(Science, Technology and Engineering)
SAF/AQR
1060 Air Force Pentagon
Washington, DC 20330-1060

Dr. Robert G. Henderson
Director
JASON Program Office
The MITRE Corporation
1820 Dolley Madison Blvd
Mailstop W553
McLean, VA 22102

J A S O N Library [5]
The MITRE Corporation
Mail Stop W002
1820 Dolley Madison Blvd
McLean, VA 22102

Mr. O' Dean P. Judd
Los Alamos National Laboratory
Mailstop F650
Los Alamos, NM 87545

Dr. Bobby R. Junker
Office of Naval Research
Code 111
800 North Quincy Street
Arlington, VA 22217

Dr. Martha Krebs
Director
Energy Research, ER-1, Rm 7B-058
1000 Independence Ave, SW
Washington, DC 20858

Lt Gen, Howard W. Leaf, (Retired)
Director, Test and Evaluation
HQ USAF/TE
1650 Air Force Pentagon
Washington, DC 20330-1650

Dr. Arthur Manfredi
ZETA Associates
10300 Eaton Drive
Suite 500
FairfaxVA 22030-2239

Dr. George Mayer
Scientific Director
Army Research Office
4015 Wilson Blvd
Tower 3, Suite 216
Arlington, VA 22203-2529

Ms. M. Jill Mc Master [3]
Central Intelligence Agency
DS&T/IPO
2S30, Plaza A
Washington, DC 20505

Dr. Thomas Meyer
DARPA/DIRO
3701 N. Fairfax Drive
Arlington, VA 22203

Dr. Julian C. Nall
Institute for Defense Analyses
1801 North Beauregard Street
Alexandria, VA 22311

Dr. Ari Patrinos [5]
Associate Director
Biological and Environmental Research
SC-70
US Department of Energy
19901 Germantown Road
Germantown,MD 207874-1290

Dr. Bruce Pierce
USD(A)D S
The Pentagon, Room 3D136
Washington, DC 20301-3090

Mr. John Rausch [2]
Division Head 06 Department
NAVOPINTCEN
4301 Suitland Road
Washington, DC 20390

DISTRIBUTION LIST

Records Resource
The MITRE Corporation
Mailstop W115
1820 Dolley Madison Blvd
McLean, VA 22102

Dr. Peter D. Zimmerman
Science Advisor
ACDA
320 21st Street, NW
Washington, DC 20451

Dr. Fred E. Saalfeld
Director
Office of Naval Research
800 North Quincy Street
Arlington, VA 22217-5000

Dr. Dan Schuresko
Chief
Advanced Technology Group/
CMS
Washington, DC 20505

Dr. John Schuster
Submarine Warfare Division
Submarine, Security & Tech
Head (N875)
2000 Navy Pentagon Room 4D534
Washington, DC 20350-2000

Dr. Richard Spinrad
US Naval Observatory
Naval Oceanographers Office
3450 Massachusetts Ave, NW
Washington, DC 20392-5421

Dr. Michael A. Stroschio
US Army Research Office
P. O. Box 12211
Research Triangle Park, NC 27709-2211

Dr. George W. Ullrich [3]
ODUSD(S&T)
Director for Weapons Systems
3080 Defense Pentagon
Washington, DC 20301-3080

Dr. David Whelan
Director
DARPA/TTO
3701 North Fairfax Drive
Arlington, VA 22203-1714